




鉄筋コンクリートU形ふた



種別	呼び名	寸法 (mm)								縦鉄筋		横鉄筋		参考重量 (kg)
		b	b ₁	t	t ₁	t ₂	L	r	b ₂	径	本	径	本	
1種	150	210	35	35	30	5	600	15	75	2.6	3	2.6	5	10
	180	250	40	40	35	5	600	15	75	2.6	3	2.6	6	14
	240	330	50	45	40	5	600	15	90	3.2	4	3.2	6	21
	300	400	55	60	50	10	600	15	100	3.2	4	4.0	6	32
	360	460	55	65	55	10	600	18	120	3.2	4	5.0	6	41
	450	560	60	70	60	10	600	18	120	4.0	5	6.0	5	54
	600	740	75	75	65	10	600	18	150	4.0	6	6.0	6	77
2種	150	210	35	90	80	10	600	15	75	6.0	3	6.0	7	26
	180	250	40	90	80	10	600	15	75	6.0	4	D10	5	31
	240	330	50	100	85	15	600	15	90	6.0	5	D10	5	44
	300	400	55	100	85	15	600	15	100	6.0	6	D10	6	54
	360	460	55	100	85	15	600	18	120	6.0	7	D10	7	63
	450	560	60	120	100	20	600	18	120	D10	6	D10	7	92
	600	740	75	150	130	20	600	18	150	D10	6	D13	6	153

*径線6.0の代わりにD6を使用してもよい。